REGULATOR
GAUGES

SPECIFICATONS:

Accuracy: +-2.5% of full scales for 1.5“

Range available: -30”Hg-0 (vacuum)
-30”Hg-0 - 6000psi (compound)
0 - 15psi ~ 6000psi (pressure)

Working Pressure :
- Steady : 3/4 of full scale
- Fluctuating : 2/3 of full scale
- Short time : full scale

Operating Temperature :
- Ambient: -4°F to 140°F
- Media: max. 140°F

Service Fluid : • Compatible gases & liquids 111AL

Housing : • Gold steel case

Windows : • Thread plastic window

Bourdon Tube :
- Copper- alloy
- 30”Hg-800psi C-Type
- 800 psi to 6000 psi Coil –Type

Movement : • Semi-copper alloy

Thread : • BSP , BSPT, NPT, or metric thread

Dials : • Aluminum

Scale Unit : • Bar or Bar + Psi

LOREM IPSUM DOLOR SIT AMETCONSE

sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. At vero eos et

GOLD STEEL CASE

SIZE	MOUNT BRASS	WORKING PSI	PART NUMBER
2”	1/8”	450	G-2-200SF
	1/4”	450	G-2-4000SF
	Acrylic Replacement Face		AC-20
2-1/2”	1/8”	450	G-2-200SF
	1/4”	450	G-2-200SF
	Acrylic Replacement Face		AC-25

SEALFAST
THE SIMPLE SOLUTION

sales@sealfast.com 800.231.0734 sealfast.com

5603 Harvey Wilson Drive, Houston, TX 77020

The SIMPLE SOLUTION

GAUGES