

KE TURN BACK COMBINATION NIPPLES

Hose Nipples are used in fluid applications where a safe, consistent, and reliable end configuration is required. They feature an interlock groove that is designed to accommodate "interlocking crimped ferrules" for ultimate holding power. The hose barsbs have a graduated serration pattern for added coupling integrity (when used with crimp ferrules) and a rounded end barb to reduce the potential of gouging the tube during installation.



SIZE	WORKING PSI	PLATED IRON	316 SS
		PART #	PART #
1"	150	SF100SPTBC	SF100SSPTBC6
1-1/4"	150	SF125SPTBC	SF125SSPTBC6
1-1/2"	150	SF150SPTBC	SF150SSPTBC6
2"	150	SF200SPTBC	SF200SSPTBC6
2-1/2"	150	SF250SPTBC	SF250SSPTBC6
3"	150	SF300SPTBC	SF300SSPTBC6
4"	150	SF400SPTBC	SF400SSPTBC6
6"	150	SF600SPTBC	SF600SSPTBC6
8"	150	SF800SPTBC	SF800SSPTBC6
10"	150	SF1000SPTBC	SF1000SSPTBC6
12"	150	SF1200SPTBC	SF1200SSPTBC6

*** WARNING:** Working Pressures may vary depending on how the couplings are attached to the hose assembly. Before operation, always check the hose assembly for proper attachment and that couplings are in working order. A Turned Back Nipple, when used in a Floating Flange Assembly, allows the flange to be aligned without stressing (twisting) the hose. This generally increases the hose service life by eliminating a common cause of premature hose failure. For use with Lap Joint Flanges

General Uses: Working pressures may vary with type and clamping system used to install couplings. Combination Nipples are recommended for low pressure discharge and suction service for compatible liquids. NOT for compressible products such as Air, Nitrogen and Steam. * All blank end & grooved combination nipples are made using Schedule 40 pipe. Seal Fast Crimp Combination Nipples are to be used with Seal Fast Ferrules and Crimp Sleeves. They are designed with an Interlock System which allows the Ferrule to be permanently attached to the coupling. **WORKING PRESSURE 150 PSI**

PIPE FITTINGS & VALVES



SEALFAST
THE SIMPLE SOLUTION

The
SIMPLE
SOLUTION



sales@sealfast.com

800.231.0734

sealfast.com

5603 Harvey Wilson Drive, Houston, TX 77020