

**NEW
PRODUCT**

SIZES
2 1/2" x 2"



TYPE CR - Female Coupler x Reducing Shank

PRODUCT LINE

TYPE CR - Female Coupler x Reducing Shank



**TYPE
CR**

Size	WORKING PSI	ALUMINUM	316 SS	316 SS - Locking
		Part #	Part #	Part #
1-1/2" x 1"	100	CR 1510AL	CR 1510SS	---
2" x 1"	---	CR 2010AL	---	---
2" x 1-1/4"	150	CR 2012AL	---	---
2" x 1-1/2"	150	CR 2015AL	CR 2015SS	---
2-1/2" x 1-1/2"	150	CR 2515AL	---	---
New 2-1/2" x 2"	150	CR 2520AL	---	---
3 x 2"	100	CR 3020AL	CR 3020SS	---
3" x 2-1/2"	150	CR 3025AL	CR 3025SS	CR 3025SSK
3" x 4"	150	CR 3040AL	---	---
4" x 3"	150	CR 4030AL	CR 4030SS	---

WARNING: Cam & Groove Couplings should NOT be used with any compressed gas, including steam or air. Metal fittings should not be used with Polypropylene Cam & Groove. Working Pressures may vary depending on how the couplings are attached to the hose assembly. Before operation, always check the hose assembly for proper attachment and that couplings are in working order.

**BUY
NOW**

<https://products.sealfast.com/item/type-cr/aluminum-cr-reducing-c-cam-and-groove-couplings/cr-2520a1>

The
**SIMPLE
SOLUTION**



COUPLINGS +