

**NEW
PRODUCT**

SIZES
1 1/4"
2 1/2"

CRIMPTEK - Combo Nipples - Grooved

PRODUCT LINE

CRIMPTEK - Combo Nipples

GROOVED

Size	WORKING PSI	STEEL		316 SS	
		* Part #		* Part #	
1"	200	SF100SGC		SF100SSG6C	
1-1/4"	200	SF125SGC		SF125SSG6C	
1-1/2"	200	SF150SGC		SF150SSG6C	
2"	200	SF200SGC		SF200SSG6C	
2-1/2"	200	SF250SGC		SF250SSG6C	
3"	200	SF300SGC		SF300SSG6C	
4"	200	SF400SGC		SF400SSG6C	
6"	200	SF600SGC		SF600SSG6C	

* WARNING: Working Pressures may vary depending on how the couplings are attached to the hose the hose assembly for proper attachment and that couplings are in working order.

General Uses:

Working pressures may vary with hose type and clamping system used to install couplings. Combination Nipples are recommended for low pressure discharge and suction service for compatible liquids. NOT for compressible products such as Air, Nitrogen and Steam. *All blank end & grooved combination nipples are made using Schedule 40 pipe. Seal Fast Crimp Combination Nipples are to be used with the Seal Fast Ferrules and Crimps Sleeves on pages 36-39 of this catalog. They are designed with an Interlock System which allows the Ferrule to be permanently attached to the coupling. **WORKING PRESSURE 200 PSI**

**BUY
NOW**

sealfast.com/category/grooved

The
**SIMPLE
SOLUTION**



COUPLINGS +