

**NEW
PRODUCT**

EPDM /PVC SUCTION SERIES LW

FEATURES

- Medium duty, light-weight construction; retains flexibility in cold weather. Smooth-bore tube to minimize material build up & resist a variety of chemicals in agricultural & sanitary industries. Slight corrugated outer cover promotes abrasion resistance.
- Designed for use in waste management, construction, agriculture, marine and manufacturing industries.

ID	OD	Length	BLACK EPDM W/GREEN POLYETHYLENE					
			40 - 50 PSI					
			Working PSI	Vacuum Hg	Bend Radius	Lbs per 100ft	Part #	List ft.
1-1/2"	1.84"	100'	50	150	3"	20	LW-150	
2"	2.43"	20' / 25' / 33' / 100'	50	150	4"	25	LW-200	
3"	3.52"	20' / 25' / 33' / 100'	45	129	5"	34	LW-300	
4"	4.62"	100'	40	114	9"	20	LW-400	

ASSEMBLIES - EPDM /PVC SUCTION - SERIES LW

STANDARD

- Aluminum Cam Locks
- Plated Steel NPT KCs
- Plated Steel Crimp Sleeves

AVAILABLE ON REQUEST *MOQ MAY APPLY*

• **Lengths:** 10' | 25' | 50'

• Assemblies:

Cam Locks: Material – 356-T6 Aluminum, Brass, 304SS, 316SS, Iron
Type – Crimp, Self-Locking

KC Nipples: Material – Plated Steel, 316SS
Type – Grooved, Weld Bevel, Turnback

Hose Attachment: Material – Plated Steel, 316SS
Type – Sleeves, Ferrules, Band Clamps

20' STOCKED

STANDARD

ID	Length	CAM LOCK C X E - ALUMINUM			CAM LOCK C X E - POLYPROPYLENE BANDS - SS		CAM LOCK C (ALUMINUM) X NPT KC NIPPLE (PLATED STEEL)	
		# of Bands	PART #	PRICE	PART #	PRICE	PART #	PRICE
2"	20'	2	LW20020CEAL		---		LW20020CIALXMP	
	25'	2	LW20025CEAL		LW20025CEPP		LW20025CIALXMP	
3"	20'	2	LW30020CEAL		---		LW30020CIALXMP	
	25'	2	LW30025CEAL		LW30025CEPP		LW30025CIALXMP	
4"	20'	3	LW40020CEAL		---		LW40020CIALXMP	
	25'	3	LW40025CEAL		LW40025CEPP		LW40025CIALXMP	



SEALFAST
THE SIMPLE SOLUTION

The
SIMPLE
SOLUTION

sales@sealfast.com

800.231.0734

sealfast.com

5603 Harvey Wilson Drive, Houston, TX 77020

1001
THERMOPLASTIC HOSE